

NORTENT FABRICS



FABRIC	ARCX-N100E	Arcx-N150B	ARCX-N300	ARCX-N400	ARCX-N700	POLYCOTTON
MODEL	<ul style="list-style-type: none"> • HELLEREN 	<ul style="list-style-type: none"> • SKJUL 	<ul style="list-style-type: none"> • BIVUAKK • VERN 1, Ly 1 • VERN 2, Ly 2 • VERN 3, Ly 3 	<ul style="list-style-type: none"> • LAVVO 4 • GAMME 4 	<ul style="list-style-type: none"> • GAMME 6 • GAMME 8 • LAVVO 6 • KOIE 7 	<ul style="list-style-type: none"> • GAMME 6 PC • GAMME 8 PC • LAVVO 6 PC • VERN 1 PC
INNER TENT			<ul style="list-style-type: none"> • 30 Denier breathable ripstop nylon • DWR coating 	<ul style="list-style-type: none"> • 30 Denier breathable ripstop nylon • DWR coating 	<ul style="list-style-type: none"> • 30 Denier breathable ripstop nylon • DWR coating 	<ul style="list-style-type: none"> • 30 Denier breathable ripstop nylon • DWR coating
OUTER TENT	<ul style="list-style-type: none"> • 10 D ripstop nylon. Ultralight (290g), • 28 g/m2 • Tear strength: Min 6 kg (ISO 13937-4) • HH:2000 mm, coated on both sides. UV 35+ 	<ul style="list-style-type: none"> • 15 Denier ripstop nylon • Tear strength: Min 3 kg (ISO 13937-4) • HH: 14000 mm. UV 35+ • HH: Breathable membrane (15000 g/m2 7 24h) 	<ul style="list-style-type: none"> • 30 Denier ripstop nylon • Tear strength: Min 16 kg (ISO 13937-4) • HH: 3000 mm. Silicone coated on both sides. UV 35+ 	<ul style="list-style-type: none"> • 40 Denier ripstop silnylon • Tear strength: Min. 19 kg (ISO 13937-4) • HH 3000 mm, Silicone coated on both sides. UV 35+ 	<ul style="list-style-type: none"> • 70 Denier ripstop silnylon • Tear strength. Min 28 kg (ISO 13937-4) • HH 3000 mm, Silicone coated on both sides. UV 35+ 	<ul style="list-style-type: none"> • 65/35 polycotton • 210 Oxford nylon • 213 g/m2 • Waterproof • Mould proof
FLOOR		<ul style="list-style-type: none"> • 70 Denier nylon • HH 10000 mm 	<ul style="list-style-type: none"> • 70 Denier nylon • HH 10000 mm 	<ul style="list-style-type: none"> • 70 Denier nylon • HH 10000 mm 	<ul style="list-style-type: none"> • 70 Denier nylon • HH 10000 mm 	<ul style="list-style-type: none"> • 210D Oxford nylon • HH 5000 mm